



Data Sheet | Model: **Armorgard FlamBank FBC2**



- Strong hazardous vault for storing hazardous goods safely and securely
- Keyed alike 5-lever deadlocks
- Unique external and internal anti-jemmy system
- Robust construction using 2mm and 3mm steel
- Hydraulic gas arms to assist with the lid opening
- Autolatch lid stay to secure the lid in the open position
- High and low level ventilation to prevent build-up of fumes
- Flame arrester gauze fitted
- The FlamBank is built to the specification of 30 minute fire resistance
- Suitable for storing flammable equipment or chemicals
- Fully welded sump to comply with COSHH regulations and prevent any leakages
- Fork lift skids with fixing holes to add castors and make it a mobile unit
- Facilities to fix the unit in position
- Comes complete with 1 shelf
- Complete with relevant signage

Product	Armorgard FlamBank FBC2
Internal dimensions	675x605x1185
External dimensions (including	765x675x1270
protrusions)	
Weight (kg)	107
Colour	PillarBox Red; RAL-3020
Finished Coating	Powder Coat with anti-corrosive undercoat
Material	Steel
Material Thickness	2mm and 3mm
Locking mechanism	Highly Secure, keyed alike 5-Lever Deadlock
Does it have Forklift Skids?	Yes
Does it have Gas Arms?	Yes
Newton Loading of Gas Arms	450N
Safety stay	Yes
Quantity of keys supplied	3 Robust keys
Optional Extras Available	Castors, shelves
Quantity of Shelves as standard	1
Are Castors standard or optional extra	Optional Extra
How are the Castors fitted?	Quick-fix bolt on Castor kit
Sump capacity	50
Safety Signage	Hazardous Goods Sign
Fire resistant?	Up to 30 minutes