



COBAdeluxe Workplace Mat

Fatigue relief for heavy-duty workstations









- · Creates a safe and very comfortable standing surface.
- Its thickness makes it a durable mat that can withstand impact.
- · Quickly cover large areas if used as a connecting system.
- Made from hardwearing rubber providing longevity.
- · Excellent slip resistance in wet areas.
- Open drainage holes for spilt liquids make it ideal for wet workplaces.
- Available as a single mat or can be linked together with connectors for larger areas.
- Use of optional edges is recommended to reduce the risk of trips.
- Slip tested to DIN 51130.









Parts

Part Number	Size	Colour	Weight
DM010002	1 m x 1.5 m	Black	16.40 kg
P240-L1093-C09	Long edge 1565 mm x 50 mm	Black	0.95 kg
P240-L1092-C09	Short edge 1074 mm x 50 mm	Black	0.65 kg
P240-L1092-C09- YE	Short edge 1074 x 50 mm	Yellow	0.65 kg
P240-L1093-C09- YE	Long edge 1565 x 50 mm	Yellow	0.95 kg
DM010003	Connector	Black	0.3 kg

Technical Specification

Material	Natural rubber
Surface Finish	Circular pattern construction for extra grip and holes to allow drainage
Product Height	18.5 mm
Product Weight	15kg
Hole Size	24 mm (large), 13 mm (small)
Operating Temperature	-20°C to +50°C
Resistance to Chemicals	Not resistant to fat and mineral oil
Environmental Resistance	Suitable for indoor and outdoor environments
UV Resistance	Yes
Typical Applications	General industrial, Bars, Catering environments
Installation Method	Loose Lay
Accessories	Bevelled edges
Cleaning Method	Wash down with hose or pressure wash
Country of Origin	Sri Lanka

Storage and application	Mat should be covered by polythene	
Tensile Strength	3 МРа	
Elongation	250%	
Application Temperature	-30°C to 50°C	
Slip Tested to	DIN 51130 - R10	
Manufacturing process	Compression moulding	

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)116 240 1088 or email sales@cobaeurope.com