



Diamond Tread Anti Fatigue Mat

Fatigue relief for welding professionals



- Welders need relief from standing like any other professional.
- The heavy-duty top surface is both resilient and fire tested, whilst the soft foam underlayer provides cushioning for the feet.
- Ideal for welding bays and demanding industrial use.
- Flame retardant top surface (tested to BS EN 13501-1) – so weld sparks aren't an issue.
- Loose lay – can be moved easily.
- Bevelled edges help avoid creating a trip risk.



Parts

Part Number	Size	Colour	Weight
DTB010001	0.6 m x 0.9 m	Black	3.70 kg
DTB010002	0.9 m x 1.5 m	Black	9.32 kg
DTB010003	0.9 m x 18.3 m	Black	113.00 kg
DTB010003C	0.9 m x per linear metre	Black	6.50 kg

Technical Specification

Material	Vinyl top surface with PVC foam backing (fusion bonded, not glued)
Surface Finish	Diamond pattern
Product Height	15 mm
Roll Length	18.3 m
Operating Temperature	0°C to +55°C
Environmental Resistance	Suitable for dry indoor environments. Will withstand welding splatter and spillages of other hot materials.
Typical Applications	Welding bays
Installation Method	Loose lay
Cleaning Method	Brush/mop the top surface
Fire Tested to	BS EN 13501-1 Class Cfl - s1
Country of Origin	China

