

## Safety Cage Series 2.0

---



[Representative image of product]

### Product Description

It's not a ladder, it's the Little Giant® Safety Cage®. With the Cage, you can access workspaces that would typically require tying-off, scaffolding or lifts, all with less time and labour than other climbing solutions. The Cage has a comfortable standing surface with a fully enclosed toe kick and wraparound enclosure, making it faster, safer and less expensive than many scaffolding or lift options. Plus, because you can work hands-free, the Safety Cage is perfect for jobs like maintaining large HVAC equipment or installing stage lighting.

### Features

- Enclosed Safety Cage® eliminates tie-off requirement
- Compliant with industry rules for three points of contact
- Ground Cue® bottom rung alert lets you know when you've reached the bottom rung
- Tip & Glide™ wheels increase portability during transportation
- Wheel lift castors allow you to roll the ladder while fully deployed, and lock in place for secure climbing
- Light enough to work on weight-limited stages and upper floors
- Non-conductive fibreglass rails are ideal when working around electricity
- Hi-Viz green fibreglass increases the Cage's visibility, preventing accidental bumping

### Specifications

- Brand: Little Giant Ladder Systems
- Warranty: 1-year
- Max Load: 150kg
- Material: Fibreglass
- Commodity Code: 3926.90.9930
- Country of Origin: CN
- Recommended Usage: Intensive

### Common Dimensions

- Tread Depth: 76mm
- Distance Between Treads: 300mm
- Storage Depth: 150mm
- Top Platform Tread (LxW): 460 x 530mm
- Handrail Height: 1070mm

### Availability & Delivery

Stock item. Bulky delivery up to 7 days.  
(See exceptions, if applicable, overleaf)

# Safety Cage Series 2.0

## Product Dimensions

SKU	Treads <sup>2</sup>	Approx. Working Height <sup>1</sup> (mm)	Platform Height (mm)	Closed Height (mm)	Width (mm)	Open Depth (mm)	Nett Weight (kg)
1304-092	2	2160	560	1960	830	860	23.3
1304-094	4	2780	1180	2540	900	1210	27.0
1304-096	6	3300	1700	3150	980	1560	31.8
1304-098	8	3860	2260	3760	1050	1910	35.1
1304-100	10	4440	2840	4360	1120	2260	42.8

<sup>1</sup> Working height is calculated as 1,600mm plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of 75° degrees.

<sup>2</sup> Treads includes top platform step/top cap tool tray tread

## Shipping Dimensions

SKU	Barcode	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m <sup>3</sup> )	Gross Weight (kg)
1304-092	5060798010105	2050	880	210	0.379	27.7
1304-094	5060798010112	2630	910	210	0.503	33.4
1304-096	5060798010129	3200	1000	210	0.672	39.2
1304-098	5060798010136	3800	1070	210	0.854	43.9
1304-100	5060798010143	4360	1100	210	1.007	52.5

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed.  
This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.

**TB Davies (Cardiff) Ltd**, Lewis Road, Cardiff, CF24 5EB, GB. +44(0)29 2132 0000 [www.tbdavies.co.uk](http://www.tbdavies.co.uk) Registered in England No.534073, VAT Reg. No.GB134144207  
Awarded Silver by Investors in People, 2018. An ISO 9001 Registered Company. Members of The Ladder Association and PASMA.