



## COBAmat® Light

Standing the test of time, our original safety matting



- The original premium multi-purpose safety mat widely used across industry today.
- An ideal choice for longer production lines, or for covering mezzanine floors.
- Available in four vibrant colours and four weave (hole) sizes to suit the application.
- Vinyl strips are interwoven, rather than welded, for better flexibility and lower risk of breaking.
- Cross-ribbed grip to reduce slipping.
- Fully reversible for added longevity.
- Suitable for use in wet and dry environments, or where swarf and debris cause problems.
- Fire tested to BS EN 13501-1 and slip tested to DIN 51130.
- Widely used in a range of industrial and non-industrial environments, both wet and dry.
- 30 mm x 30 mm hole size.

View our Anti-Slip range.

## Parts

Part Number	Size	Colour	Weight (kg)
CO010605	0.6 m x 5 m	Black	11
CO010610	0.6 m x 10 m	Black	22
CO010905	0.9 m x 5 m	Black	16
CO010910	0.9 m x 10 m	Black	32
CO011205	1.2 m x 5 m	Black	22
CO011210	1.2 m x 10 m	Black	44
CO020605	0.6 m x 5 m	Blue	11
CO020610	0.6 m x 10 m	Blue	22
CO020905	0.9 m x 5 m	Blue	16
CO020910	0.9 m x 10 m	Blue	32
CO021205	1.2 m x 5 m	Blue	22
CO021210	1.2 m x 10 m	Blue	44
CO030605	0.6 m x 5 m	Red	11
CO030610	0.6 m x 10 m	Red	22

## Technical Specifications

<b>Material</b>	PVC
<b>Surface Finish</b>	Cross ribbed lattice
<b>Product Height</b>	12 mm
<b>Hole Size</b>	30 mm x 30 mm
<b>Min. Operating Temperature</b>	-20°C
<b>Max. Operating Temperature</b>	+60°C
<b>Resistance to Chemicals</b>	PVC is resistant to many different chemicals, alkalis and general industrial chemicals. PVC resists alcohols, aliphatic hydrocarbons, oils, weak acids, strong mineral acids and alkalis. PVC resists oil and grease if properly cleaned. PVC does not resist organic solvents, ketones, esters and aromatic hydrocarbons. Please contact us for more specific details
<b>Environmental Resistance</b>	Suitable for wet and dry environments, indoors or outdoors

Part Number	Size	Colour	Weight (kg)
CO030905	0.9 m x 5 m	Red	16
CO030910	0.9 m x 10 m	Red	32
CO031205	1.2 m x 5 m	Red	22
CO031210	1.2 m x 10 m	Red	44
CO040605	0.6 m x 5 m	Green	11
CO040610	0.6 m x 10 m	Green	22
CO040905	0.9 m x 5 m	Green	16
CO040910	0.9 m x 10 m	Green	32
CO041205	1.2 m x 5 m	Green	22
CO041210	1.2 m x 10 m	Green	44

UV Resistance	Resistant to UV, but please note that red is not colourfast in direct sunlight
Typical Applications	General industrial, Engineering, Machine tool areas where swarf prevalent
Installation Method	Loose lay, reversible
Accessories	Factory fitted edging where required
Cleaning Method	Pressure hose with mild detergent if required
COO (Country of Origin)	UK
Slip Tested to	DIN 51130 - R10

## Additional Information



Workstation Ramp Slip Test DIN 51130



Workstation Fire Test EN ISO 11925



Workstation Fire Test EN ISO 9239



Workstation Fire Test BS EN 13501