



## Bubblemat Nitrile

Smart anti-fatigue mat with a distinctive bubbled surface



- High-quality anti-fatigue mat.
- Raised bubble patterned surface encourages movement and stimulates circulation, reliably preventing signs of fatigue.
- Increased work safety due to slip resistance.
- NBR rubber (nitrile) for good resistance to oil, lubricants and chemicals.
- Available as individual mats or interlocking sections for longer production lines

## Parts

Part Number	Size	Colour	Weight (kg)
BF010001N	0.6 m x 0.9 m	Black (Nitrile)	5
BF010002N	0.9 m x 1.2 m	Black (Nitrile)	11
BF010003N	0.6 m x 0.9 m	Black (Nitrile)	5
BF010004N	0.6 m x 0.9 m	Black (Nitrile)	5

## Technical Specifications

Material	NBR
Surface Finish	Bubble
Product Height	14 mm
Min. Operating Temperature	-20°C
Max. Operating Temperature	+50°C
Resistance to Chemicals	NBR offers excellent resistance to oils and chemicals
Environmental Resistance	Suitable for predominantly dry environments
UV Resistance	Yes
Typical Applications	General industrial
Installation Method	Loose lay interlocking mats

<b>Cleaning Method</b>	Use a high pressure hose (not exceeding 60psi) to remove the dirt and debris on the mats. For best results use a mild detergent (pH 4.0-9.0) to clean the mats. Do not use steam or degreasers or caustic chemicals. Do not mechanically scrub the mats
<b>COO (Country of Origin)</b>	LK
<b>Tensile Strength</b>	3 MPa
<b>Elongation</b>	250%
<b>Application Temperature</b>	-30°C to 50°C
<b>Manufacturing process</b>	Compression moulding

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email [sales@cobaeurope.com](mailto:sales@cobaeurope.com)

[www.cobaeurope.com](http://www.cobaeurope.com)