

COBAguard

Self-adhesive floor protection film with hard floor and carpet options



- Adaptable floor protection film for maintenance and show houses etc, to keep floors clean.
- Film is reverse wound on the roll for rapid installation, saving you time.
- Can be installed by hand for smaller rooms / staircases or with an applicator for larger areas.
- Does not leave marks or residues - no cleaning required after use.
- Self-adhesive polyethylene protection film.
- Can be branded with your logo upon request.



Parts

Part Number	Size	Colour	Weight (kg)
CGC00001	0.6 m x 25 m	Clear	1.5
CGC00002	1.2 m x 25 m	Clear	2.65
CGC00003	0.6 m x 50 m	Clear	2.75
CGC00004	1.2 m x 50 m	Clear	5.2
CGC00005	0.6 m x 100 m	Clear	4.9
CGC00006	1.2 m x 100 m	Clear	12
CGH00001	0.6 m x 25 m	Clear	1
CGH00002	1.2 m x 25 m	Clear	2
CGH00003	0.6 m x 50 m	Clear	2
CGH00004	1.2 m x 50 m	Clear	6

Technical Specifications

Material	PE (LDPE and LLDPE) film
Surface Finish	Smooth
Product Height	sol dur : 50 micron, moquette : 90 micron
Max. Operating Temperature	+60°C
Environmental Resistance	Suitable for indoor environments
Typical Applications	Temporary protection of carpets and hard floors
COO (Country of Origin)	CN

Part Number	Size	Colour	Weight (kg)
CGH00005	0.6 m x 100 m	Clear	4
CGH00006	1.2 m x 100 m	Clear	8

Adhesion Strength	1-2 kg / 50 mm
Storage and application	The product should be protected against direct sunlight and extremes in temperature and humidity and stored upright in its original packaging. The film should be applied within a 3 month period from the delivery date. The film should be removed within 30 days from the date of lamination. Surface preparation is important. The substrate should be clean and free from residue, such as dust and oil, when the tape is applied in order to achieve optimum adhesion. Do not press too hard when applying. This may cause the end of the tape to peel. If applying to surfaces treated with machining oil, degrease the surface carefully. Any remains will be a cause for surface contamination or adhesive residue.
Tensile Strength	≥45 N/mm
Elongation	≥300%
Application Temperature	Cold temperatures can affect the peel strength. Please apply the film at room temperature (+10°C to +30°C).

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@cobaeurope.com

www.cobaeurope.com