




COBAGRiP® Sheet

GRP flooring is the ideal solution to combat slip hazards such as liquids and ice



- An easy to install anti-slip solution for internal and external areas.
- Simply bond or screw the GRP flooring onto the existing floor surface.
- Available in a range of colours which meet the Equality Act requirements, including black, grey and yellow.



Styles Available



Yellow



Grey



Black

Part Number	Size	Colour	Weight (kg)
GRP010001	1.2 m x 2.4 m	Black	23.6
GRP010002	1.2 m x 1.2 m	Black	10.08
GRP010003	0.8 m x 1.2 m	Black	7.7
GRP060001	1.2 m x 2.4 m	Grey	23.6
GRP060002	1.2 m x 1.2 m	Grey	10.08
GRP060003	0.8 m x 1.2 m	Grey	6.7
GRP070001	1.2 m x 2.4 m	Yellow	23.6
GRP070002	1.2 m x 1.2 m	Yellow	10.08
GRP070003	0.8 m x 1.2 m	Yellow	6.7

Material	GRP
Product Height	5 mm
Min. Operating Temperature	-50°C
Max. Operating Temperature	+90°C
Environmental Resistance	Suitable for indoor and outdoor environments
Typical Applications	External walkways
Installation Method	Bond or screw to surface
Cleaning Method	COBAGRiP should be almost maintenance free in most outside environments. Natural elements will have the effect of cleaning COBAGRiP. Brushing and flushing with a mild detergent solution may be desirable now and again to restore appearance.
Fire Tested to	DIN 13501: Bfl - s1 (2018) & EN ISO 11925-2:2020 & EN ISO 9239-1:2010 (both 2021)
COO (Country of Origin)	CN
Slip Tested to	DIN 51130 - R13 & BS 7976-2 - low slip potential

Additional Information



Installation Guide



COBAGRiP EN ISO11925 2 2020 Reaction to Fire



COBAGRiP Pendulum Slip Test BS 7676



COBAGRiP EN ISO9239 1 2010 Reaction to Fire



COBAGRiP Fire Test EN13501 1 2018



COBAGRiP Ramp Slip Test DIN 51130

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@cobaeurope.com

www.cobaeurope.com