




COBAGRiP® Light

GRP flooring solution for use on undulating surfaces



- An easy to install anti-slip solution for internal and external areas.
- Silicon carbide surface for high anti-slip protection it's ideal for use on undulating surfaces including factory walkways, ramps and bridges.
- Simply bond or screw the GRP flooring onto the existing floor surface.
- Available in a range of colours which meet the Equality Act requirements, including black, grey and yellow.



Styles Available



Yellow



Grey



Black

Parts

Part Number	Size	Colour	Weight (kg)
GRP010001L	1.2 m x 2.4 m	Black	17
GRP010002L	1.2 m x 1.2 m	Black	10.08
GRP010003L	0.8 m x 1.2 m	Black	6

Technical Specifications

Material	GRP
Product Height	2.4 mm
Min. Operating	-50°C

Part Number	Size	Colour	Weight (kg)
GRP060001L	1.2 m x 2.4 m	Grey	17
GRP060002L	1.2 m x 1.2 m	Grey	10
GRP060003L	0.8 m x 1.2 m	Grey	6
GRP070001L	1.2 m x 2.4 m	Yellow	17

Temperature	
Max. Operating Temperature	+90°C
Environmental Resistance	Suitable for indoor and outdoor environments
Typical Applications	External walkways
Installation Method	Bond or screw to surface
Cleaning Method	COBAGRiP should be almost maintenance free in most outside environments. Natural elements will have the effect of cleaning COBAGRiP. Brushing and flushing with a mild detergent solution may be desirable now and again to restore appearance.
Fire Tested to	DIN 13501: Bfl - s1 (2018) & EN ISO 11925-2:2020 & EN ISO 9239-1:2010 (both 2021)
COO (Country of Origin)	CN
Slip Tested to	DIN 51130 - R13 & BS 7976-2 - low slip potential

Additional Information

	Installation Guide		COBAGRiP EN ISO11925 2 2020 Reaction to Fire
	COBAGRiP EN ISO9239 1 2010 Reaction to Fire		COBAGRiP Fire Test EN13501 1 2018
	COBAGRiP Pendulum Slip Test BS 7676		COBAGRiP Ramp Slip Test DIN 51130

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@cobaeurope.com

www.cobaeurope.com