






## COBAGRiP® Stair Nosing

Increase stair safety with highly visible anti-slip stair nosing



- Durable and easy to install on both existing and new-build steps.
- A hard wearing, gritty surface available in bright colours helps protect against slips and trips whilst meeting the Equality Act requirements (DDA).
- Manufactured with chamfered back edge for additional safety.



### Parts

| Part Number | Size                   | Colour | Weight (kg) |
|-------------|------------------------|--------|-------------|
| GRP010001N  | 3 m x 55 mm x 55 mm    | Black  | 1.8         |
| GRP010002N  | 2 m x 55 mm x 55 mm    | Black  | 1.2         |
| GRP010003N  | 1.5 m x 55 mm x 55 mm  | Black  | 0.9         |
| GRP010004N  | 1 m x 55 mm x 55 mm    | Black  | 0.6         |
| GRP010005N  | 0.75 m x 55 mm x 55 mm | Black  | 0.45        |

### Technical Specifications

|                            |       |
|----------------------------|-------|
| Material                   | GRP   |
| Product Height             | 5 mm  |
| Min. Operating Temperature | -50°C |
| Max. Operating             | +90°C |

| Part Number | Size                   | Colour       | Weight (kg) |
|-------------|------------------------|--------------|-------------|
| GRP010701N  | 3 m x 55 mm x 55 mm    | Black/Yellow | 1.8         |
| GRP010702N  | 2 m x 55 mm x 55 mm    | Black/Yellow | 1.2         |
| GRP010703N  | 1.5 m x 55 mm x 55 mm  | Black/Yellow | 0.9         |
| GRP010704N  | 1 m x 55 mm x 55 mm    | Black/Yellow | 0.6         |
| GRP010705N  | 0.75 m x 55 mm x 55 mm | Black/Yellow | 0.45        |
| GRP070001N  | 3 m x 55 mm x 55 mm    | Yellow       | 1.8         |
| GRP070002N  | 2 m x 55 mm x 55 mm    | Yellow       | 1.2         |
| GRP070003N  | 1.5 m x 55 mm x 55 mm  | Yellow       | 0.9         |
| GRP070004N  | 1 m x 55 mm x 55 mm    | Yellow       | 0.6         |

| Temperature                     |                                                                                                                                                                                                                                                 |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Environmental Resistance</b> | Suitable for indoor and outdoor environments                                                                                                                                                                                                    |
| <b>Typical Applications</b>     | External steps                                                                                                                                                                                                                                  |
| <b>Installation Method</b>      | Bond or screw to surface                                                                                                                                                                                                                        |
| <b>Cleaning Method</b>          | COBAGRiP should be almost maintenance free in most outside environments. Natural elements will have the effect of cleaning COBAGRiP. Brushing and flushing with a mild detergent solution may be desirable now and again to restore appearance. |
| <b>Fire Tested to</b>           | DIN 13501: Bfl - s1 (2018) & EN ISO 11925-2:2020 & EN ISO 9239-1:2010 (both 2021)                                                                                                                                                               |
| <b>COO (Country of Origin)</b>  | CN                                                                                                                                                                                                                                              |
| <b>Slip Tested to</b>           | DIN 51130 - R13 & BS 7976-2 - low slip potential                                                                                                                                                                                                |

## Additional Information

|                                                                                    |                                             |                                                                                     |                                              |
|------------------------------------------------------------------------------------|---------------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------|
|    | Installation Guide                          |    | COBAGRiP EN ISO11925 2 2020 Reaction to Fire |
|  | COBAGRiP EN ISO9239 1 2010 Reaction to Fire |  | COBAGRiP Fire Test EN13501 1 2018            |
|  | COBAGRiP Pendulum Slip Test BS 7676         |  | COBAGRiP Ramp Slip Test DIN 51130            |

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email [sales@cobaeurope.com](mailto:sales@cobaeurope.com)

[www.cobaeurope.com](http://www.cobaeurope.com)