



Insertion Black Rubber

Features embedded textile reinforcement for added increased tensile strength and tear resistance



- Suitable for use in air, hot water and hydraulic services.
- A popular gasket material for applications with high compression loads.

Parts

Part Number	Size	Colour	Weight (kg)
IRS00001	1.4 m x 10 m x 1.8 mm	Black	47
IRS00002	1.4 m x 10 m x 3 mm	Black	71.15
IRS00003	1.4 m x 10 m x 4.5 mm	Black	94.5
IRS00004	1.4 m x 10 m x 6 mm	Black	130.5
IRS00005	1.4 m x 5 m x 10 mm	Black	110.5
IRS00006	1.4 m x 5 m x 12 mm	Black	131.3

Technical Specifications

Material	SBR
Surface Finish	Smooth
Product Height	1.8 mm-25 mm
Roll Length	5 m, 10 m
Min. Operating Temperature	-30°C
Max. Operating Temperature	+70°C
Other Product Performance Information	Test Temperature: 25°C Relative Humidity: 35% Correlation criterion: GB/T528-1998 GB/T3512-1989 GB/T531-1992
COO (Country of Origin)	CN
Tensile Strength	3.4 MPa
Elongation	190%
Specific Weight (g/cm³)	1.6
Shore A Hardness	70 ±5

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@cobaeurope.com

www.cobaeurope.com