

## Para Shotblast Rubber

Unbeatable tensile strength, natural tan rubber



- Excellent resistance to wear and abrasion.
- Widely used as protective screening for shotblasting.
- Also used in strip or gasket form where durability is essential.
- 45 degrees shore A hardness.
- Tensile strength at break: 15 Mpa.
- Elongation at break: 400%.



### Parts

Part Number	Size	Colour	Weight (kg)
PRS00001	1.4 m x 10 m x 3 mm	Tan	47
PRS00002	1.4 m x 10 m x 6 mm	Tan	85
PRS00003	1.4 m x 5 m x 10 mm	Tan	84
PRS00004	1.4 m x 5 m x 12 mm	Tan	98

### Technical Specifications

<b>Material</b>	Natural rubber
<b>Surface Finish</b>	Smooth
<b>Product Height</b>	1 mm-25 mm
<b>Roll Length</b>	5 m, 10 m
<b>Min. Operating Temperature</b>	-40°C
<b>Max. Operating Temperature</b>	+80°C
<b>Typical Applications</b>	Shotblasting screens
<b>Other Product Performance Information</b>	Test Temperature 25°C Relative Humidity 35% Correlation criterion GB/T528-1998 GB/T3512-1989 GB/T531-1992
<b>COO (Country of Origin)</b>	CN

