



## **Toughrib Contract**

Ribbed entrance matting on a roll designed to scrape dirt and wipe moisture



- A popular choice for flooring contractors requiring versatile rolls of entrance carpet.
- Debris and moisture are captured in the ridges and can be vacuumed for easy maintenance.
- Adaptable carpet entrance matting that can be used in recessed matwells or on pedestrian walkways.
- 100% polypropylene pile is durable and suitable for heavy-duty use.



## Styles Available



Brown



Grey





Charcoal

Blue

## Parts

| Part Number | Size                   | Colour   | Weight (kg) |
|-------------|------------------------|----------|-------------|
| TR010006    | 2 m x 30 m roll        | Charcoal | 61          |
| TR010006C   | 2 m x per linear metre | Charcoal | 2.03        |
| TR020006    | 2 m x 30 m roll        | Blue     | 61          |

## **Technical Specifications**

| Material       | 75% PP, 25% PE     |
|----------------|--------------------|
| Backing        | PD                 |
| Surface Finish | 2-rib design       |
| Product Height | 6.5 mm +15% / -10% |
|                |                    |

| Part Number | Size                   | Colour | Weight (kg) |
|-------------|------------------------|--------|-------------|
| TR020006C   | 2 m x per linear metre | Blue   | 2.03        |
| TR050006    | 2 m x 30 m roll        | Brown  | 61          |
| TR050006C   | 2 m x per linear metre | Brown  | 2.03        |
| TR060006    | 2 m x 30 m roll        | Grey   | 61          |
| TR060006C   | 2 m x per linear metre | Grey   | 2.03        |

| Product Weight  | 1.93 kg / m <sup>2</sup>        |  |
|---|---------------------------------|--|
| Roll Length   | 35 m                            |  |
| Pile Height   | 2.5 mm ± 10%                    |  |
| Durability  | Low to medium traffic entrances |  |
| Pile Weight   | 0.62 kg / m <sup>2</sup>        |  |
| Typical Applications                                    | Entrance areas                  |  |
| Other Product Performance Information                   | CE approved                     |  |
| COO (Country of Origin)                                 | NL                              |  |
| Adhesive recommended by F.Ball for permanent bond       | F3                              |  |
| Adhesive recommended by F.Ball for heavy-duty/wet areas | F74, F81 or F84                 |  |

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@cobaeurope.com

www.cobaeurope.com