



www.wearwell.com

FOUNDATION Modular Aluminum Work Platform KIT - Diamond-Plate Traction Surface

Group FP3

[FOUNDATION](#) cuts down on time, labor, customization, and costly manpower! This modular platform system comes in a range of heights, lengths and widths that makes assembly and installation easier than ever before. Any shape and size is possible, down to 1.5 foot (.45m) sections. **Perfect for raised access flooring applications.**

All components, including the aluminum frame, resist corrosion. This surprisingly lightweight system provides all the support your team demands and more! Each 2.75" (7 cm) thick tile boasts a load rating of 400 lbs. and is manufactured of 100% recycled polypropylene to stand up to a wide range of chemicals.

[Available in 3 surface patterns](#), the Diamond-Plate pattern offers more than rugged good looks - it provides undeniable traction!

- 100% recycled (post-consumer) polypropylene tiles
- Structural aluminum frame
- Chemical and corrosion resistant
- 400 lb. (181.5kg) load capacity per tile
- Elevates employees over cords, hoses, and other hazards
- Excellent for raised access flooring applications
- Widths: 18" and 36" (46 cm and 91 cm)
- Lengths: 18", 36", 54", 72" (46 cm, 91 cm, 137 cm, 183 cm)
- Stocked Heights: 4", 8" and 12" (10 cm, 20 cm, 30 cm)
- Custom heights available
- Installed correctly, raised flooring improves worker safety and ergonomics
- Made in the USA
- Patent pending

Learn more about our FOUNDATION Modular Work Platforms in our blog [Work Platform Materials That Make the Difference](#).
[FOUNDATION Assembly Videos](#)

Wearwell Categories	Platform
Suitable Environment	Dry, Wet, Wet/ Dry
Customisation Level	C3
Solid or Drainage	Drainage
Compound	Polypropylene/Aluminum
Recycled	54%
Warranty	1 year

Property	Test / Result
Flammability	FMVSS 302: Pass B
Taber Abrasion	ASTM D3884: 0% @1000 cycles
Temperature Range	32-160F
Coefficient of Friction	ASTM F2913-19: 1.09 dry, 0.90 wet
Compression Deflection	Not Applicable
Tear Strength	Not Applicable

ESD Rating	Not Applicable
Dielectric Strength	Not Applicable

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
FP3x12x18x18BK		Aluminum/Black	12"	12" x 18" x 18"	Y	Each
FP3x12x18x36BK		Aluminum/Black	12"	12" x 18" x 36"	Y	Each
FP3x12x18x54BK		Aluminum/Black	12"	12" x 18" x 54"	Y	Each
FP3x12x18x72BK		Aluminum/Black	12"	12" x 18" x 72"	Y	Each
FP3x12x36x18BK		Aluminum/Black	12"	12" x 36" x 18"	Y	Each
FP3x12x36x36BK		Aluminum/Black	12"	12" x 36" x 36"	Y	Each
FP3x12x36x54BK		Aluminum/Black	12"	12" x 36" x 54"	Y	Each
FP3x12x36x72BK		Aluminum/Black	12"	12" x 36" x 72"	Y	Each
FP3x4x18x18BK		Aluminum/Black	4"	4" x 18" x 18"	Y	Each
FP3x4x18x36BK		Aluminum/Black	4"	4" x 18" x 36"	Y	Each
FP3x4x18x54BK		Aluminum/Black	4"	4" x 18" x 54"	Y	Each
FP3x4x18x72BK		Aluminum/Black	4"	4" x 18" x 72 "	Y	Each
FP3x4x36x18BK		Aluminum/Black	4"	4" x 36" x 18"	Y	Each
FP3x4x36x36BK		Aluminum/Black	4"	4" x 36" x 36"	Y	Each
FP3x4x36x54BK		Aluminum/Black	4"	4" x 36" x 54"	Y	Each
FP3x4x36x72BK		Aluminum/Black	4"	4" x 36" x 72 "	Y	Each
FP3x8x18x18BK		Aluminum/Black	8"	8" x 18" x 18"	Y	Each
FP3x8x18x36BK		Aluminum/Black	8"	8" x 18" x 36"	Y	Each
FP3x8x18x54BK		Aluminum/Black	8"	8" x 18" x 54"	Y	Each
FP3x8x18x72BK		Aluminum/Black	8"	8" x 18" x 72"	Y	Each
FP3x8x36x18BK		Aluminum/Black	8"	8" x 36" x 18"	Y	Each
FP3x8x36x36BK		Aluminum/Black	8"	8" x 36" x 36"	Y	Each
FP3x8x36x54BK		Aluminum/Black	8"	8" x 36" x 54"	Y	Each
FP3x8x36x72BK		Aluminum/Black	8"	8" x 36" x 72"	Y	Each