



www.wearwell.com

## FOUNDATION Open Drainage Work Platform KIT

### Group FP2

[FOUNDATION](#) cuts down on time, labor, customization, and costly manpower! This modular platform system comes in a range of heights, lengths and widths that makes assembly and installation easier than ever before. Any shape and size is possible, down to 1.5 foot (.45m) sections.

All components, including the aluminum frame, resist corrosion. This surprisingly lightweight system provides all the support your team demands and more! Each 2.75" (7 cm) thick tile boasts a load rating of 400 lbs. and is manufactured of 100% recycled polypropylene to stand up to a wide range of chemicals.

Available in 3 surface patterns, this Open version allows free passage of fluids, debris and airflow. Integrated traction points provide long-lasting, reliable [slip prevention](#).

- 100% recycled (post-consumer) polypropylene tiles
- Structural aluminum frame
- Chemical and corrosion resistant
- 400 lb. (181.5kg) load capacity per tile
- Elevates employees over cords, hoses, and other hazards
- Widths: 18" and 36" (46 cm and 91 cm)
- Lengths: 18", 36", 54", 72" (46 cm, 91 cm, 137 cm, 183 cm)
- Stocked Heights: 4", 8" and 12" (10 cm, 20 cm, 30 cm)
- Custom heights available
- Made in the USA
- Patent pending

Learn more about the sustainability of our FOUNDATION Modular Work Platforms in our blog [FOUNDATION Work Platforms for a Sustainable Future](#). [FOUNDATION Assembly Videos](#)

<b>Wearwell Categories</b>	Platform
<b>Suitable Environment</b>	Slippery
<b>Customisation Level</b>	C3
<b>Solid or Drainage</b>	Drainage
<b>Compound</b>	Polypropylene/Aluminum
<b>Recycled</b>	54%
<b>Warranty</b>	1 year

Property	Test / Result
Flammability	FMVSS 302: Pass B
Taber Abrasion	ASTM D3884: 0% @1000 cycles
Temperature Range	32-160F
Coefficient of Friction	ASTM F2913-19: 1.03 dry, 0.83 wet
Compression Deflection	Not Applicable
Tear Strength	Not Applicable
ESD Rating	Not Applicable
Dielectric Strength	Not Applicable

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
FP2x12x18x18BK		Aluminum/Black	12"	12" x 18" x 18"	Y	Each
FP2x12x18x36BK		Aluminum/Black	12"	12" x 18" x 36"	Y	Each
FP2x12x18x54BK		Aluminum/Black	12"	12" x 18" x 54"	Y	Each
FP2x12x18x72BK		Aluminum/Black	12"	12" x 18" x 72"	Y	Each
FP2x12x36x18BK		Aluminum/Black	12"	12" x 36" x 18"	Y	Each
FP2x12x36x36BK		Aluminum/Black	12"	12" x 36" x 36"	Y	Each
FP2x12x36x54BK		Aluminum/Black	12"	12" x 36" x 54"	Y	Each
FP2x12x36x72BK		Aluminum/Black	12"	12" x 36" x 72"	Y	Each
FP2x4x18x18BK		Aluminum/Black	4"	4" x 18" x 18"	Y	Each
FP2x4x18x36BK		Aluminum/Black	4"	4" x 18" x 36"	Y	Each
FP2x4x18x54BK		Aluminum/Black	4"	4" x 18" x 54"	Y	Each
FP2x4x18x72BK		Aluminum/Black	4"	4" x 18" x 72 "	Y	Each
FP2x4x36x18BK		Aluminum/Black	4"	4" x 36" x 18"	Y	Each
FP2x4x36x36BK		Aluminum/Black	4"	4" x 36" x 36"	Y	Each
FP2x4x36x54BK		Aluminum/Black	4"	4" x 36" x 54"	Y	Each
FP2x4x36x72BK		Aluminum/Black	4"	4" x 36" x 72 "	Y	Each
FP2x8x18x18BK		Aluminum/Black	8"	8" x 18" x 18"	Y	Each
FP2x8x18x36BK		Aluminum/Black	8"	8" x 18" x 36"	Y	Each
FP2x8x18x54BK		Aluminum/Black	8"	8" x 18" x 54"	Y	Each
FP2x8x18x72BK		Aluminum/Black	8"	8" x 18" x 72"	Y	Each
FP2x8x36x18BK		Aluminum/Black	8"	8" x 36" x 18"	Y	Each
FP2x8x36x36BK		Aluminum/Black	8"	8" x 36" x 36"	Y	Each
FP2x8x36x54BK		Aluminum/Black	8"	8" x 36" x 54"	Y	Each
FP2x8x36x72BK		Aluminum/Black	8"	8" x 36" x 72"	Y	Each