

## MOBILE SCISSOR LIFT TABLES



### TECHNICAL FEATURES

- Safe, light, easy to use and highly manoeuvrable
- High quality robust construction
- A range of maximum lift heights from 750mm to 1610mm
- Manual operation
- Single or double lifts available
- Heavy duty arm, bearings and hydraulics
- All wheels are fitted with sealed bearings and polyurethane tyres
- One castor fitted with a total stop brake as standard
- All models fitted with an overload valve and slow lowering valve to control lowering speed
- Each table is issued with operating instructions and a test certificate in conformance with EU Standards EN 1570 and BS:5323:1980

CAPACITY	LIFT HEIGHT	PLATFORM DIMENSIONS	OVERALL DIMENSIONS	OWN WEIGHT	CODE
<b>200kg</b>	255 - 780mm	485 x 700mm	485 x 790mm	40kg	<b>AH11A2S</b>
<b>300kg</b>	310 - 860mm	620 x 850mm	620 x 930mm	80kg	<b>AH11B3S</b>
<b>500kg</b>	330 - 950mm	610 - 920mm	610 x 1030mm	150kg	<b>AH11C5S</b>
<b>800kg</b>	345 - 940mm	610 x 920mm	610 x 1030mm	120kg	<b>AH11D8S</b>
<b>350kg</b>	425 - 1620mm	610 x 920mm	610 x 1030mm	150kg	<b>AH11E3D</b>