Spec Sheet

RUBBER ANTI SHOCK GYM TILES



The BiGDUG Rubber Anti Shock Gym Tile is manufactured with a 2-layer system, with coarse granules on the bottom, and the top 5mm using fine granules. Designed for heavyweight areas in gyms and cross fit centres to provide shock absorption, sound insulation and a non-slip surface.

Product code: BDGT30 | BDGT43



P	r	n	h	п	C.	ŀ
		•	u	ч	v	

Bigdug **Brand** Range Gym Flooring **Solid or Drainage Properties** Tough elastic, high compression resistance and impact strength **Tolerances** Length and width \pm 1.5%, thickness \pm 2 mm **Slip Resistance Dry Conditions** <105PTV- EN 13036-4:2004 **Slip Resistance Wet Conditions** <75PTV - EN 13036-4:2004 Abrasion Resistance, MG <560 - EN ISO 5470-1:2001 Tensile Strength, MPA >0.65 **Elongation at Break** >40% - EN 12230:2005 **Hardness** 55 up to 75 SHORE A - ISO 868 PN-93 / C-04206 Density 950 to 1.000kg/m3 - EN ISO 845:2010 **Fire Classification** EFL s1 (DFL & CFL Available) - NOT TESTED



Pa	ľ
ı u	ш

1 uit		
Part Code	BDGT30	BDGT43
Material	Recycled SBR rubber granules from 70% Dutch truck tires, bonded with PU	Recycled SBR rubber granules from 70% Dutch truck tires, bonded with PU
Surface Finish	Non-Slip	Non-Slip
Size	1000mm x 1000mm	1000mm x 1000mm
Product Height	30mm	43mm
Product Weight	28kg	27kg
Product Colour	Black (other colours on request)	Black (other colours on request)
Country of Origin	Netherlands	Netherlands
ICN Code	40169100	40169100

Note: Images are not to scale.