

ALEV 250/20K-SG-AS

Heavy duty wheel, with 'Blickle EasyRoll' elastic solid rubber tyres, with aluminium wheel centre, non-marking, grey, antistatic

EAN 4047526347321

ID 911575

Customs tariff number 87169090



Tyre:

- high-quality elastic solid rubber "Blickle EasyRoll" in smooth rolling quality, hardness 65 Shore A
- very good operational comfort
- very good floor preservation, low-noise operation
- low rolling resistance
- colour grey, non-marking
- vulcanised onto the wheel centre

Wheel centre:

- die-cast aluminium

Other features:

- high chemical resistance to many aggressive substances, except oils
- operating temperature: -20 °C to +80 °C, temporarily up to +100 °C, reduced load capacity over +60 °C
- electrical conductivity (ohmic resistance) $\leq 10^7 \Omega$



Technical data:

Wheel Ø (D)	☉	250 mm
Wheel width	⊥	50 mm
Load capacity at 4 km/h	⊞	550 kg
Load capacity at 6 km/h	⊞	440 kg
Load capacity at 10 km/h	⊞	270 kg
Load capacity (static)	⊞	1,375 kg
Bearing type	☉	ball bearing
Axle bore Ø (d)		20 mm
Hub keyway (T1)	·0·	60 mm
Temperature resistance min		-20 °C
Temperature resistance max		80 °C
Tread and tyre hardness		65 Shore A
Unit weight	⊞	2.2 kg
Non-marking		✓
Non-staining		✓
Antistatic	⊞	✓
ESD		✓
Electrically conductive	⊞	✗
Corrosion-resistant		✗
Heat-resistant	⊞	✗
Suitable for autoclaves		✗

Tread and tyre hardness

■ ■ ■ ■ ■ 65 Shore A

Rolling resistance

■ ■ ■ ■ ■ very good

Wear resistance

■ ■ ■ ■ ■ good

Operating noise / floor surface preservation

■ ■ ■ ■ ■ very good

