

Specifications	Fixed	Swivel/Braked
Wheel Dia.	125 mm	125 mm
Wheel Width	32 mm	32 mm
Castor Width	60 mm	60 mm
Bolt-Ø	N/A	28 mm
Bolt Length	N/A	45 mm
Offset	N/A	41 mm
Swivel Interference	N/A	262 mm
Overall height	160 mm	163 mm
Size of Plate	77 x 67 mm	N/A
Plate Hole Centres	61,5/56 x 51,5/46,5 mm	N/A
Plate Hole	8,5 mm	N/A
Swivel Radius	N/A	131 mm
Dome-Ø	60 mm	60 mm
Temperature	- 20 / + 60 °C	- 20 / + 60 °C
Standard	EN_12530	EN_12530
Hardness of Tread	Shore A 83	Shore A 83
Materials	Fork made of pressed steel, bright zinc plated, blue passivated, wheel axle with nut, plate fitting. Wheel centre made of Polypropylene Tread: thermoplastic rubber, grey non-marking, precision ball bearing, with threadguards	Swivel castor with total lock, tail end of castor, housing made of pressed steel, bright zinc plated, blue passivated, double ball bearing swivel head, wheel axle with nut, solid plug fitting. Wheel centre made of Polypropylene Tread: thermoplastic rubber, grey nonmarking, precision ball bearing , with threadguards