

Flexi Tred Xtra



Extra thick heavy-duty switchboard matting with a textured surface that insulates from electrical shock.



Introducing our latest electrical insulation matting: Flexi Tred Xtra, a thicker version of proven Flexitred that provides certified electrical resistance up to 7,500V (ASTM D178 Class I)

A Heavy-duty matting broad ribbed textured matting, Flexi Tred is the ideal matting in manufacturing and process industries, where electrical safety is required. Manufactured from 100% vinyl. Flexitred Xtra is very hard-wearing, easy to clean and provides good slip resistance whilst being naturally resistant to acids, chemicals and oils. Available in 10 metre rolls and with four colours options as standard to enhance working environments.



Features:



Textured, broad-rib surface



7,500V working voltage



Hard-wearing vinyl sheets




Made from flexible PVC



Supplied in a convenient roll format



Benefits:



Good slip and wear resistance



Insulates from electrical shock



Resistant to chemicals, acids and oils



Easy to cut to fit on site; contours to the subfloor



Quick to install



Plastic Extruders Ltd.

Russell Gardens, Wickford
Essex, SS11 8DN
+44 (0) 1268 571 116

UK + USA manufactured
matting products:
plastexmatting.com



Standard sizes:

Product	Flexi Tred Xtra
Height	4.6mm (3/16")
Standard roll options	10 x 1m (33' x 3'3")
Weight	5.5kg/m ² (1.26lb/sq.ft)

Tolerances:

	Height (+/- 0.5mm)	Length (0+0.3m)	Width (+/- 1cm)
Flexi Tred Xtra Xtra	4.6 mm	10 m	100 cm

All dimensions are nominal

Technical information:

Chemical	Resistant to most acids, alkalines and oils. You can read more about specific chemical resistances by downloading this information sheet .
Composition	Flexible Polyvinyl Chloride (PVC)
Environment	Flexi Tred Xtra is 100% recyclable. We don't use any substances included in the SVHC list under REACH in any of our matting products.
Electrical	ASTM D178 Class I (7,500V working voltage)
Fire	UL 94. Horizontal burning test. Classification 94HB
Reversion	Thermoplastic shrinkage can result in size reductions up to 2%. This may be accelerated in hot environments. You can read more about the causes of shrinkage by downloading this information sheet .
Thermal	Designed to function at temperatures from -23°C and up to +60°C. Slight size variation may occur at temperature extremes.
UV light	Resistant to PVC degradation.
Warranty	Two years. Visit our policies page for more information about warranties

Installation:

Flexi Tred Xtra's one-piece construction means installation is simple:

- Supplied in convenient roll format
- Easy to cut to size and shape
- Contours to the sub floor

Cleaning:


Keeping Flexi Tred Xtra looking good is easy:

- Easy to clean with a vacuum or mop
- No special cleaning tools needed

Colours:



Blue



Light grey



Brown



Black

More colours
available
upon request