

Parent Code

HANROUGHDESC

Specifications	Hangcha Lithium Powered Rough Terrain Pallet Truck
Operator Type	Pedestrian
Rated Capacity	1500kg
Load Centre Distance	500mm
Load Distance, Centre of Drive Axle to Fork	667mm
Wheelbase	1197mm
Service Weight	440kg
Axle Loading, Laden Front/Rear	460/1480kg
Axle Loading, Unladen Front/Rear	240/200kg
Tyre Type	Solid Rubber
Tyre Size, Front	Ø250 × 80mm
Tyre Size, Rear	Φ399 × 104mm
Wheels (Front/Rear)	1x / 2
Rear Tread	1230mm
Lift Height	250mm
Overall Length	1773mm
Length to Face of Forks	703mm
Overall Width	546 / 1390mm
Fork Dimensions	35 / 100 / 1070mm
Distance Between Fork Arms	210–850mm
Ground Clearance, Centre of Wheelbase	100mm
Aisle Width for Pallets 800 × 1200 Lengthways	2112mm
Turning Radius	1410mm
Travel Speed, Laden/Unladen	5.5 / 5.5 km/h
Lift Speed, Laden/Unladen	0.046 / 0.061 m/s
Lowering Speed, Laden/Unladen	0.056 / 0.058m/s
Parking Brake	Electric
Drive Motor Rating S2 60 min	1kW
Lift Motor Rating at S3 15%	1.5kW
Battery Voltage / Nominal Capacity K5	48 / 20 V/Ah
Type of Drive Unit	DC