

WHEEL

PU ENVIRONMENTAL POLYURETHANE

Diameter (mm)	Tread Width (mm)	Bearing Type	Hub Depth (mm)	Bore (mm)	Load Capacity (KG)
---------------	------------------	--------------	----------------	-----------	--------------------



ICMCSW4D20

400MM PU MICRO-CELLULAR DIAMOND PATTERN

400

85



66

20

300

ICMCSW4D25

400MM PU MICRO-CELLULAR DIAMOND PATTERN

400

85



66

25

300

ICMCSW4D254

400MM PU MICRO-CELLULAR DIAMOND PATTERN

400

85



66

25.4

300

ICMCSW3D20

370MM PU MICRO-CELLULAR RIB PATTERN

370

85



66

20

180

ICMCSW3D25

370MM PU MICRO-CELLULAR RIB PATTERN

370

85



66

25

180

ICMCSW3D254

370MM PU MICRO-CELLULAR RIB PATTERN

370

85



66

25.4

180

PLASTIC CENTRED

ICMCPW2D20

260MM PU MICRO-CELLULAR DIAMOND PATTERN

260

85



75

20

120

Black Pneumatic Tyres on Red Centre
Normal operational running speed Below 6 kph
Temperature: -20°C - +80°C
Centres: Steel or Plastic